

**MAXLITE™**  
**PRODUCT**  
**FOCUS**




**DIMMAX 15W**  
60 Watt Replacement



**DIMMAX 20W**  
75 Watt Replacement

**DIMMAX 25W**  
100 Watt Replacement

Patented Air Gap  
US Patent #  
6,204,602



**Application:**

- Table and floor lamps
- Track and recessed lighting
- Ceiling fixtures
- Hanging pendant

**Recommended for:**

- Residential
- Hotel/Motel
- Retail
- Restaurant
- Office
- Conference Rooms

**R30/R40**

Optional  
Snap-On  
Aluminum  
Reflector



**Benefits:**

- Continuous dimming down to 10%
- Air-gap, amalgam technology, heat sink, and higher temperature (130°C) rated components for greater heat tolerance
- Automatic shut-off function protects lamp against adverse conditions
- Works with existing dimming controls
- Long life – lasts 10,000 hours
- Compact size and brighter light suitable for most fixtures

**MaxLite™**

19 Chapin Road  
Building B  
Pine Brook, NJ 07058-2005  
www.maxlite.com  
Tel: (973) 244-7300  
Fax: (973) 244-7333  
E-mail: info@maxlite.com

ISO 9002 Certified



FCC Certified

**DIMMAX SPECIFICATIONS**

Watts	Order Code	Description	Lumens (Lm)	Efficacy (LM/W)	Lamp Life (Hrs)	Color / CRI* (°K) / (Ra)	Operating Temp. (°F)	Pack Type	Case Qty	Dimensions (w" x mol")
15	01504	MLS15EADWW Spiral	900	60	10,000	2800 / 82	0-140	Box	12	2.5 x 5.3
20	02004	MLS20EADWW Spiral	1200	60	10,000	2800 / 82	0-140	Box	12	2.5 x 5.8
25	01104	MLS25EADWW Spiral	1500	60	10,000	2800 / 82	0-140	Box	12	2.5 x 6.2
	30903	YREF/R30AL R30 Reflector Aluminum (15W only)								
	30923	YREF/R40AL R40 Reflector Aluminum								

\*CRI = Color Rendering Index

Notes: (1) Not suitable for dimming circuits or timing devices. (2) Use in recessed or enclosed lighting fixtures with elevated line voltage may shorten life.