

All2easy[®]
One2flush[®]

Dual Flush Valve • Installation Instructions • Fits all toilet types (A, B or C)

Let's get started saving water!
Anyone can install it (steps #1-5)



- ▶ (1) Turn off water supply and flush toilet. ▶ (2) Remove the existing handle and flapper.

If the flush valve looks like this...



A) Flat Flapper Valve

Use the flat gasket smooth side down,

Insert basket, flat gasket and toggle bolt assembly through flapper valve hole until you hear the toggle click. Tighten basket assembly so that basket will not turn.



Flat Gasket

No need to remove the tank!


If the flush valve looks like this...



B) Angled Flapper Valve


Use the angled gasket with white line pointing to center of the overflow tube.

Insert basket, angled gasket and toggle bolt assembly through flapper valve hole until you hear the toggle snap into place. Tighten basket assembly so that basket will not turn.



Angled Gasket

If you have a new toilet or if the flush valve looks like this...



C: Mansfield valve

You'll need to take the tank off and replace the entire valve system. The adjustable overflow tube will fit all size toilet tanks. Follow the directions for new toilet tanks on our web page. www.one2flush.com.



C

- ▶ (3) Insert One2flush[®] dual-flush canister into basket and turn to secure.

95% of all toilets – assemble kit inside the tank with one simple tool...and a snap fit.



A



B

All you need is a screwdriver. Everything else is here.

Dual flush canister



- ▶ (4) Attach handle through existing square hole in tank wall with handle pointing down, lock the control unit in place. (Handle has a reverse screw direction). Place decal on tank lid.

- ▶ (5) Turn water on.

Packaged in Michigan



ASSEMBLED IN THE USA
Some parts made in China.



One2flush[™]
save water, save money

One2products LLC, PO Box 400 Galesburg, MI 49053
www.one2products.com

All2easy[®] Kit Contents: (1) One2flush[®] dual flush canister and handle, (1) overflow tank attachment, (1) One2flush[®] basket, (1) One2flush[®] toggle, (1) bolt, (1) flat gasket and (1) One2flush[®] angled gasket.

WARRANTY: This One2flush[®] product has a limited warranty for a period of 5 years. For complete details please visit our website at www.one2flush.com

