

POLYKEN® 367-17

UL181B-FX Foil Mastic Tape

POLYKEN®

POLYKEN® 367-17
FOILMASTIC™ SEALANT
LISTED
181B-FX
82P4
FOR CLASS 1 DUCT

POLYKEN® 367-17
FOILMASTIC™ SEALANT
LISTED
181B-FX
82P4
FOR CLASS 1 DUCT

BERRU

PLASTICS
CORPORATION

AND SUBSIDIARIES

TAPES AND COATINGS DIVISION



POLYKEN® 367-17

UL181B-FX Foil Mastic Tape

Berry Plastics Corporation, the industry leader for innovative materials for HVAC, is proud to offer Polyken® 367-17 UL181B-FX Foil Mastic Tape. Designed to meet the needs of virtually all duct sealing applications, 367-17 is especially well suited for use on *rigid sheet metal duct* and *flexible duct* installations. In addition, 367-17 performs well in a variety of sealing and waterproofing applications both indoors and out.

POLYKEN® 367-17

48mm x 31M
ITEM NO. 652122
24 rolls/case
27 cases/pallet

3" x 100Ft
ITEM NO. 652123
16 rolls/case
27 cases/pallet

FOR MORE INFORMATION ON
POLYKEN® 367-17 OR OTHER POLYKEN®
BRAND PRODUCTS FOR THE HVAC
MARKET, CONTACT YOUR AREA SALES
MANAGER.

SPECIAL FEATURES

- UL181B-FX listed - Printed for easy identification
- Long-term indoor & outdoor performance
- Non-Staining Adhesive
- Paintable 2mil Foil Backing
- Excellent adhesion to all surfaces
- Superior all weather performance
- Low VOC
- Can contribute toward EA Credit 1 (Optimize Energy Performance) and EQ Credit 4.1 (Low Emitting Materials, Adhesives and Sealants) under LEED®

Thickness: 17mils (431.8 μ)

Adhesion to Steel: 90 oz/in (9.85 N/cm)

Adhesion to Backing : 40 oz/in (4.38 N/cm)

Tensile Strength: 23 lb/in (40.28 N/cm)

Installation Temperature: 40 to 100 °F (4 to 37°C)

Operating Temperature: 30 to 200 °F (-1 to 93°C)

VOC Content: <1 g/L



Contributes toward
LEED® Certification Credits.



For more information:
25 Forge Parkway
Franklin, MA 02038
Phone 508.918.1600 • Fax 508.918.1901



www.berryplastics.com

Corporate:
P.O. Box 959 • 101 Oakley St.
Evansville, IN 47710
Phone 812.306.2000 • Fax 812.424.0128