Catalog Number



35,000 Hours average rated life, 120Volts

Applications:

Ideal for dimmable 6", 5" & 4" downlight applications



Perfect for retrofit or new construction recessed downlight applications

Features and Benefits

 Ideal for replacing dimmable 65W and 85W incandescent alternatives in 5" and 6" recessed cans.

4" unit ideal for replacing 50W incandescent alternatives in a 4" recessed can.

- Exceeds all industry standards ENERGY STAR rated.
- Smooth, uniform dimming.
- Highly efficient LEDs and Driver.
- Long Life: 35,000 hours.
- Consistent color within 3 MacAdam ellipse tolerance.
- UL approved for damp locations.
- Easy installation and integrated trim.



Specifications							
	14W	12W	10W				
Recessed Downlight Size:	5", 6"	5", 6"	4"				
Input Line Voltage:	120 VAC	120 VAC	120 VAC				
Input Power	14 W	12 W	10 W				
Input Line Frequency	50/60HZ	50/60HZ	50/60HZ				
Lamp Life (Rated)	35,000 hrs	35,000 hrs	35,000 hrs				
Minimum Starting Temp	-20℃	-20°C	-20℃				
Maximum Operating Temp	40°C	40°C	40°C				





LED12DR5627K LED12DR5630K LED14DR5627K LED14DR5630K

Warranties and Certifications:	Item#	Description	Life	Replacement	Voltage	Wattage	Lumens	LPW	ССТ	CRI	Case Qty
	Downlight Retrofits compatible with 5" & 6" recessed cans.										
LED12DR5627K	LED12DR5627K	LED 12W 5"/6" Recessed Downlight - 2700K	35,000	65	120	12	650	54.2	2700K	82	6
c(UL)us	LED14DR5627K	LED 14W 5"/6" Recessed Downlight - 2700K	35,000	85	120	14	800	57.1	2700K	82	6
	LED12DR5630K	LED 12W 5"/6" Recessed Downlight - 3000K	35,000	65	120	12	670	55.8	3000K	82	6
✓ YEAR *	LED14DR5630K	LED 14W 5"/6" Recessed Downlight - 3000K	35,000	85	120	14	820	58.6	3000K	82	6
WARRANTY	Downlight Retrofits compatible with 4" recessed cans.										
	LED10DR427K	LED 10W 4" Recessed Downlight - 2700K	35,000	60	120	10	600	60.0	2700K	82	6
*Based on 12 hours usage per day	LED10DR430K	LED 10W 4" Recessed Downlight - 3000K	35,000	60	120	10	620	62.0	3000K	82	6