

# LED Plug In

## 11.5 Watt 5000K 2-Pin LPD11M/G24d/850 LED Plug In



### PRODUCT DESCRIPTION

EarthTronics 11.5 watt LED, LPD11M/G24d/850 easily replaces 18 watt G24d-2 base compact fluorescent lamps and provides 33% energy savings. It is physically the same form factor as the CFQ18W/G24d that it replaces. This 2-pin lamp produces 1100 lumens and works directly on the existing magnetic ballast. No rewiring necessary. Instant on, no warm up time and a long service life make this lamp an easy choice in many applications. Available colors include 3000K, 4000K and 5000K and the CRI rating is >80. The unique design illuminates nearly identically to the bulb it replaces and can be used in any rotation or orientation in open fixtures. The 25,000 hour rated life provides 3 times the service life of a typical compact fluorescent lamp. For use only on single lamp ballast. Not for use in enclosed fixtures.

### PRODUCT FEATURES

- Same form factor as the PL lamp it replaces.
- Light distribution pattern is nearly identical to PL lamps.
- Works directly on magnetic ballasts for easy “plug & play” installation.
- LED provides instant on and full brightness – no waiting.
- Also available in 3000K and 4000K color temperatures.

### Applications:

- Recessed downlights
- Wall sconce
- Vanity fixtures
- Surface mount ceiling & wall fixtures
- Outdoor post lamps
- Outdoor flood lights

### Ordering Code:

- 10179
- 12 pack inner, 48 pack master

### Model:

- LPD11M/G24d/850

### Replaces:

- GE F18DBX/850/ECO
- Philips PL-C18W/850/Alto
- Sylvania CF18DD/850
- Any PL lamp utilizing the G24d-2 base, 2-pin

### Cautions:

- Not for use on 2 lamp ballast. Intended for 1 lamp per ballast.
- Not for use in enclosed fixtures.
- This 2-pin LED lamp is intended for use on Magnetic ballast.
- Not for use with dimmer controls.
- Not for use with emergency lighting.

#### Electrical

Watt	11.5 watt
------	-----------

Power Factor	> 0.50
--------------	--------

Ballast required	Magnetic
------------------	----------

Base Type	G24d-2, 2-Pin
-----------	---------------

Min. Start Temp	0° F
-----------------	------

Max. Operating Temp	120° F
---------------------	--------

#### Light

Initial Lumens	1100
----------------	------

Lumens per Watt	95 lpw
-----------------	--------

Color Temperature	5000K
-------------------	-------

Color Rendering (CRI)	82
-----------------------	----

Beam Angle	Full radial
------------	-------------

#### Agency Approvals

UL	Yes
----	-----

RoHS	Yes
------	-----

FCC	Yes
-----	-----

#### Product Details

Warranty	10 years, 6 hours per day
----------	---------------------------

Mercury Content	No Hg
-----------------	-------

Overall Length	6.6"
----------------	------