



Energetic Lighting's E3-FMA series of LED round flushmount fixtures are designed to emulate the look and feel of traditional circline fluorescent tube flushmount fixtures, but operate at a significantly lower wattage. A CCT selection switch allows the installer to switch between 3000K, 4000K, or 5000K color temperatures. Fixtures are available in multiple diameter options in both a round profile, making the choice easy for any type of application. Installation is quick and simple when mounting into standard ceiling junction boxes, and may be installed on circuits with standard wall dimmers. Constructed with a durable steel housing body and LED lifetime rating of at least 50,000 hours, this rugged flushmount is designed for many years of reliable operation.

Features

- Tool-less diffuser attachment
- Minimalistic and efficient design
- Mercury-free construction
- Suitable for Damp Location use
- Easy and secure installation
- TRIAC Dimmable to 10% output

Applications

- Multi-family and Apartments
- Overhead & Hallway lighting
- Ambient room lighting
- General lighting

Specification

Order Number	40036	40035	40034	40037
Model Number	E3LFMA22D-803050	E3MFMA14D-803050	E3SFMA12D-803050	E3XFMA32D-803050
Configuration	15" round	11" round	10" round	19" round
Beam Angle	110°	110°	110°	110°
Lumen Output	1770 LM	1115 LM	1070 LM	2490 LM
Luminous Efficacy	80 LM/W	79 LM/W	89 LM/W	78 LM/W
Input Power	22 W	14 W	12 W	32 W
Input Voltage	120 Vac	120 Vac	120 Vac	120 Vac
Power Factor	0.98	0.97	0.98	0.98
THD	<0.2	<0.2	<0.2	<0.2
Color Temp (CCT)	Selectable CCT: 3000K, 4000K, 5000K K	Selectable CCT: 3000K, 4000K, 5000K K	Selectable CCT: 3000K, 4000K, 5000K K	Selectable CCT: 3000K, 4000K, 5000K K
Color Rend (CRI)	84	84	84	84
Lifetime Rating	50000 hours	50000 hours	50000 hours	50000 hours
Warranty	5 Years	5 Years	5 Years	5 Years
Dimmability	Triac dimmable	Triac dimmable	Triac dimmable	Triac dimmable
Operating Temp	-4 to 104 (Å°F)	-4 to 104 (Å°F)	-4 to 104 (Å°F)	-4 to 104 (Å°F)
Environment	Damp Location	Damp Location	Damp Location	Damp Location
Energy Star	TBA	TBA	TBA	TBA
Safety Cert	UL	UL	UL	UL
Weight	TBA LBS	TBA LBS	TBA LBS	TBA LBS
Dimensions	15.0"(D) x 3.5" (H)	11.0"(D) x 3.0" (H)	10.2"(D) x 2.7" (H)	19.0"(D) x 4.4" (H)

Dimensions and Packaging Info

Model Number	E3LFMA22D-803050	E3MFMA14D-803050	E3SFMA12D-803050	E3XFMA32D-803050
Item UPC				
Case UPC				
Master Carton UPC				
Item(s) per pack				
packs per case				
Case per Master				
Item weight				
Case weight				
Master Weight				
Item pack dimensions				
Case dimensions				
Master dimensions				