

SCG-3MVR Smart Strip® Specifications

Features:

1. Adjustable current-sensing circuit allows a wide range of control devices to be used
2. Recessed, lighted On-Off switch with integrated 15Amp circuit breaker
3. Ground indicator light
4. Surge circuit indicator light
5. 4' 14/3 SJT power-cord
6. 45° space-saver plug
7. 4-way wall-mountable
8. EMI/RFI noise filtering: Up to 50 dB from 100 KHz to 50 MHz
9. < 1 watt stand-by current draw



Surge Protection Specifications:

1. Seven outlets total
 - a. 1 Control-outlet – Blue
 - b. 2 Always “On” outlets – Red
 - c. 4 Energy-Saving outlets w/ one transformer space – Green
2. Listed by Underwriters Laboratory 1449 3rd Edition and 1363 3rd Edition
3. Electrical Rating: 125 Volt AC 60 Hz, 15 Amperes, 1875 Watts
4. 2175 Joules of surge protection
5. Response Time: <1 nanosecond
6. Maximum Surge Voltage: 6000 Volts
7. Maximum Spike Current: 37,000 Amperes
8. 3-Line surge protection
9. Voltage Protection Rating:
 - a. 400 Volts L-N
 - b. 400 Volts L-G
 - c. 400 Volts N-G
10. Energy Savings of up to \$29.90 per year depending on connected equipment and local kWh rates.
11. \$30,000 Connected Equipment Warranty Protection – See warranty information on web-site for details; some exclusions apply.