

LEDone


Projects:

Comments:

Stadium Flood Light 600W Spec

SPECIFICATIONS:

WATTAGE:	600W
MODEL #:	LOD-SFL-600W
CERTIFICATION:	CE \ RoHS \ FCC \ ETL
INPUT VOLTAGE:	100-277VAC
POWER FACTOR:	0.9
FREQUENCY:	50-60Hz
LUMENS:	84500Lm
LUMENS EFFICACY:	100-130 lm/w
KELVIN (CCT):	3000/4000/5000/6500
THD:	<9%
CRI:	80
IP RATING:	IP67
BEAM ANGLE (DEGREE):	10/24/38/60/90 °
MATERIALS:	AL+GLASS
DRIVER:	MeanWell
LED LIGHT SOURCE	Cree
LIFE SPAN (HOURS):	>50000H
DIMMING COMPATIBLE:	0-10V
LENGTH OF WARRANTY (YEARS):	5Years
SIZE(MM):	872*457*104 mm
WORKING ENVIRONMENT:	-40°C-+80°C
POWER EFFICIENCY:	>90%
NET WEIGHT:	22 Kg
PERCENTAGE OF WATTAGE SAVED:	45 - 50%



Features:

System Light Efficacy 100 LPW. Flexible, Modular Design. Multiple Choice of Optical Lenses. Easy Installation & Maintenance. ETL, CE, RoHS, CB, and WEEE certified.

Applications:

General flood lighting, corridor lighting, security lighting, and roof top lighting. Can also be used as a high bay.

