



LED BULLET FLOOD


MLSB, MLLB SERIES



Side View



Front View



3/4 View

PRODUCT DESCRIPTION:

The outdoor rated LED bullet flood fixture is constructed with precision die cast aluminum housing and tempered glass with a 1/2" NPS threaded arm. It is ideal for use in landscape, façade and sign lighting applications. Fixture can be surface mounted directly to electrical boxes or posts with 1/2" threaded bushing.

FEATURES:

- 12W replaces up to 75 Watt Quartz
- 30W replaces up to 150 Watt Metal Halide
- Medium NEMA 5X5 field distribution
- Efficiency ranging from 70 to 86 lm/W
- 3000K and 5000K available
- 50,000 hour L70 Life
- Universal 120-277V driver
- Maintenance free
- Fixture can be surface mounted directly to electrical boxes or posts with 1/2" threaded bushing
- 5 Year Limited Warranty
- IP65 rated
- CRI: ≥75
- 1/2" NPS threaded arm with locking swivel arm
- Bronze polyester powder coat finish

CONSTRUCTION:

- Die cast aluminum body
- Sealed to keep out dirt and bugs
- Tempered shatter resistant glass lens
- Weep hole located on lower lip of fixture to prevent water buildup

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: MLLB30LED30

FAMILY		CCT	
MLSB12= 12W, 50-75W Quartz Halogen equivalent MLLB30= 30W, 100-150W Metal Halide equivalent		LED30= 3000K LED50= 5000K ¹	

NOTES:

- ¹ Only 5000K fixtures are DLC qualified



LED BULLET FLOOD
MLSB, MLLB SERIES

SPECIFICATIONS:

		MLSB12LED30	MLSB12LED50	MLLB30LED30	MLLB30LED50
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Lumens Delivered (lm)	785	810	2113	2500
	Efficacy (lm/W)	77	74	70	86
	Beam Angle (H x V)	70° x 68°	68° x 69°	63° x 62°	65° x 60°
	CCT	3000K	5000K	3000K	5000K
	Lumen Maintenance (L70)	50,000 Hours			
	Color Rendering Index (CRI)	≥75			
ELECTRICAL	Input Power (W)	10	11	30	29
	Power Factor	> 0.9			
	Input Voltage (V)	120V-277V, 50/60Hz			
	Housing	Aluminum			
PHYSICAL	Mounting	½" NPS threaded arm with locking swivel arm			
	Operating Temperature	-30°F - 104°F			
APPLICATION	Environment	IP65			
	Humidity	20% - 85% RH, non condensing			
	Warranty	5 Years			

ORDERING*:

ORDER CODE	MODEL	EFFICACY (lm/W)	OUTPUT (LUMENS)	NOMINAL POWER (WATTS)	COLOR TEMPERATURE (CCT)
74113	MLSB12LED30	77	785	12	3000K
74209	MLLB30LED30	72	2113	30	
74114	MLSB12LED50**	74	810	12	5000K
74210	MLLB30LED50**	86	2500	30	

Lighting layouts and spacing criteria available upon request

*Please contact your MaxLite representative to order products that don't have order codes listed here.

** 5000K models are DLC qualified

